26360, 80207 Inline

3/2 and 5/2 directional control valves
NG 6 and 12
Operation: elektromagnetic
Indirectly controlled
soft seal spool valves
Port size: G 1/4 and G 1/2

For single and double operated actuators

Manual override with and without detent

Simple design of soft seal spool system

Maintenance-free

Easily interchangeable solenoid

Valves and solenoids are ATEX approved
(see solenoids on page 2)



Technical data

Medium:
Compressed air, filtered *1), lubricated or non-lubricated

Operation:
Solenoid, indirectly controlled

Port size:
G 1/4 and G 1/2

Operation pressure:
max. 10 bar
(see specifications)

Flow direction:
Fixed

Mounting position:
Optional, preferably with solenoid on top

Operating temperature:

-10* to +60°C

*Please contact our technical service for use below +2°C.

Materials:

Housing: aluminium anodized
Pilot flange: plastic (POM)
Seals: NBR (Perbunan)

Ordering information

See page 2

For connector plugs see page 2
and data sheets N/UK **7.7.**002

3/2



5/2





*1) Oil recommendation: Shell Hydrol DO 32, ESSO Febis K 32 (as of 07/92) or comparable oils with DVI values < 8 (DIN 53521) and ISO viscosity class 32 to 46 (DIN 51519)

26360, 80207 Inline

3/2 and 5/2 directional control valves
NG 6 and 12
Operation: elektromagnetic
Indirectly controlled
soft seal spool valves
Port size: G 1/4 and G 1/2

For single and double operated actuators

Manual override with and without detent

Simple design of soft seal spool system

Maintenance-free

Easily interchangeable solenoid

Valves and solenoids are ATEX approved
(see solenoids on page 2)



Technical data

Medium:
Compressed air, filtered *1), lubricated or non-lubricated

Operation:
Solenoid, indirectly controlled

Port size:
G 1/4 and G 1/2

Operation pressure:
max. 10 bar
(see specifications)

Flow direction:
Fixed

Mounting position:
Optional, preferably with solenoid on top

Operating temperature:

-10* to +60°C

*Please contact our technical service for use below +2°C.

Materials:

Housing: aluminium anodized
Pilot flange: plastic (POM)
Seals: NBR (Perbunan)

Ordering information

See page 2

For connector plugs see page 2
and data sheets N/UK **7.7.**002

3/2



5/2





*1) Oil recommendation: Shell Hydrol DO 32, ESSO Febis K 32 (as of 07/92) or comparable oils with DVI values < 8 (DIN 53521) and ISO viscosity class 32 to 46 (DIN 51519)